



JDYX8.E302100 Fuses, Supplemental Certified for Canada - Component

If you notice a change to your JDYX8 Listing Card, click [here](#) to learn more.

[Page Bottom](#)

Fuses, Supplemental Certified for Canada - Component

[See General Information for Fuses, Supplemental Certified for Canada - Component](#)

KING WAHOO ELECTRONICS CO LTD

E302100

105-4 BRI 3RD ST
KEELUNG, TAIWAN

Supplemental fuses

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
5GC, 5FC	5.2 x 20.5 (0.20 x 0.81)	0.25 - 10	125Vac	10000
		0.25 - 10	250Vac	200
5GG, 5FG	20.5 x 5.2 x 3.15 (0.81 x 0.20 x 0.12)	0.5 - 1.0	125Vac	10000
		0.5 - 1.0	250Vac	35
		1.6 - 3.15	125Vac	10000
		1.6 - 3.15	250Vac	100
		4.0 - 7.0	125Vac	10000
		4.0 - 7.0	250Vac	200
5SC, 5TC	5.2 x 20.5 (0.20 x 0.81)	0.25 - 10	125Vac	10000
		0.25 - 10	250Vac	200
5SG, 5TG	5.2 x 20.5 (0.20 x 0.81)	0.25 - 7	125Vac	10000
		0.25 - 7	250Vac	200

Supplemental fuses: pigtail leads

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
3GG	11.5 x 4 x 3.15 (0.45 x 0.16 x 0.12)	0.5 - 1.0	125Vac	50
		0.5 - 1.0	250Vac	50
		2.0 - 6.3	125Vac	50
		2.0 - 6.3	250Vac	50
3SC3.15A	11.5 x 4 x 3.15 (0.45 x 0.16 x 0.12)	3.15	125Vac	50
3TC	4.0 x 11.5 (0.16 x 0.45)	0.25 - 3.15	125Vac	35
		0.25 - 3.15	250Vac	35

		4	125Vac	40
		4	250Vac	40
		5	125Vac	50
		5	250Vac	50
		6.3	125Vac	63
		6.3	250Vac	63
3TG	4.0 x 11.5 (0.16 x 0.45)	0.25 - 3.15	125Vac	35
		0.25 - 3.15	250Vac	35
		4	125Vac	40
		4	250Vac	40
		5	125Vac	50
		5	250Vac	50
		6.3	125Vac	63
		6.3	250Vac	63

Supplemental fuses: pigtail leads, filled-tube

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
HV510, HV520, HV530	5.54 x 21.1 (0.22 x 0.83)	0.1 - 20	600Vac	200
		0.1 - 20	500Vdc	300
		0.1 - 10	400Vdc	2000
HV627, HV622, HV624, HV625				
	6.76 x 26.5 (0.27 x 1.04)	0.1 - 20	250Vac	10000
		0.1 - 20	400Vdc	2000
		0.1 - 30	400Vdc	300
		0.1 - 50	75Vdc	2500

Supplemental fuses: filled-tube

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
HV510, HV520, HV530	5.2 x 20 (0.20 x 0.79)	0.1 - 20	600Vac	200
		0.1 - 20	500Vdc	300
		0.1 - 10	400Vdc	2000
HV610, HV620, HV630, HV640, HV650				
	6.3 x 31.75 (0.25 x 1.25)	0.1 - 50	250Vac	1000
		0.1 - 30	660Vac	1000
		0.1 - 30	660Vdc	1000
		0.1 - 12	600Vdc	10000
		0.1 - 12	1000Vdc	10000

HV627, HV622, HV624, HV625				
	6.3 x 25.4 (0.25 x 1.00)	0.1 - 20	250Vac	10000
		0.1 - 20	400Vdc	2000
		0.1 - 30	400Vdc	300
		0.1 - 50	75Vdc	2500

Supplemental micro fuses

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
0603	1.6 x 0.81 x 0.48 (0.06 x 0.03 x 0.02)	0.25 - 2	32Vdc	35
		2.5 - 5	24Vdc	35
1025FA	2.77 x 2.77 x 10.29 (0.11 x 0.11 x 0.41)	0.25 - 10	250Vac	50
		0.25 - 10	125Vdc	50
		12 - 15	250Vac	50
		12 - 15	60Vdc	50
1025SB	2.77 x 2.77 x 10.29 (0.11 x 0.11 x 0.41)	0.25 - 5	250Vac	50
		0.25 - 5	125Vdc	50
1206	3.2 x 1.6 x 0.7 (0.13 x 0.06 x 0.03)	0.25 - 3	32Vac	50
		0.25 - 3	63Vdc	50
		4 - 7	32Vac	50
		4 - 7	32Vdc	50
		10 - 20	24Vdc	50
KET	8.4 x 4 x 7.7 (0.33 x 0.16 x 0.30)	0.1 - 3.15	125Vac	35
		0.1 - 3.15	250Vac	35
		4	125Vac	40
		4	250Vac	40
		5	125Vac	50
		5	250Vac	50
		6.3	125Vac	63
		6.3	250Vac	63
		0.1 - 6.3	300Vac	100
		0.1 - 6.3	350Vac	100
		0.1 - 6.3	400Vac	55
KRT	8.4 x 7.7 (0.33 x 0.30)	0.25 - 3.15	125Vac	35
		0.25 - 3.15	250Vac	35
		4	125Vac	40
		4	250Vac	40

		5	125Vac	50
		5	250Vac	50
		6.3	125Vac	63
		6.3	250Vac	63
MFC	3.05 x 8.7 (0.12 x 0.34)	0.04 - 0.16	125Vac	1500
		0.04 - 0.16	250Vac	4000
		0.04 - 0.16	250Vdc	4000
		0.2 - 0.25	125Vac	1500
		0.2 - 0.25	250Vac	4000
		0.2 - 0.25	250Vdc	4000
		0.125	125Vac	1500
		0.125	250Vac	4000
		0.125	250Vdc	4000
		0.125	125Vac	1500
		0.125	250Vac	1500
		0.125	250Vac	1500
		0.04 - 0.16	250Vac	1500
MFC100mA-L	3.05 x 8.7 (0.12 x 0.34)	0.1	125Vac	1500
		0.1	125Vac	1500
		0.1	250Vac	4000
		0.1	250Vdc	4000
TCF/1025TC	2.77 x 2.77 x 10.29 (0.11 x 0.11 x 0.41)	0.5 - 2	250Vac	50
		0.5 - 2	600Vac	60

Supplemental micro fuses: pigtail leads

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
3FS	3.6 x 10 (0.14 x 0.39)	0.50 - 1.0	125Vac	35
		0.50 - 1.0	250Vac	35
		4	125Vac	40
		4	250Vac	40
		5	125Vac	50
		5	250Vac	50
		6.3	125Vac	63
		6.3	250Vac	63
		1.25 - 3.15	125Vac	35
		1.25 - 3.15	250Vac	35
MGC	2.8 x 7.0 (0.11 x 0.28)	0.25 - 7	125Vac	50
		0.25 - 7	250Vac	50

MSC	2.8 x 7.0 (0.11 x 0.28)	0.25 - 7	125Vac	50
		0.25 - 7	250Vac	50

Supplemental micro fuses: pigtail leads, filled-tube

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
3FH	3.6 x 10 (0.14 x 0.39)	1.25 - 2	125Vac	35
		1.25 - 2	250Vac	35
		1.25 - 2	250Vac	200
		1.25 - 2	250Vac	100

Supplemental micro fuses: surface mount

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
0603FF, 0603TD, 0603HI				
	1.6 x 0.81 x 0.65 (0.06 x 0.03 x 0.03)	0.1 - 1.5	63Vdc	50
		0.1 - 8	32Vdc	50
1206FF, 1206TD, 1206HV, 1206HI				
	3.2 x 1.6 x 0.65 (0.13 x 0.06 x 0.03)	0.1 - 3	125Vdc	50
		0.1 - 5	72Vdc	50
		0.1 - 5	125Vac	50
		0.1 - 7	32Vdc	50
		0.1 - 30	24Vdc	300
6125SB	2.72 x 2.72 x 6.1 (0.11 x 0.11 x 0.24)	0.5 - 7	125Vac	50
		0.5 - 7	60Vdc	50
		0.5 - 7	250Vac	50

Supplemental micro fuses: surface mount, cartridge enclosed

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
6125FA	2.72 x 2.72 x 6.1 (0.11 x 0.11 x 0.24)	0.5 - 20	125Vac	50
		0.5 - 20	32Vdc	300
		0.5 - 20	72Vdc	50
		0.5 - 20	250Vac	50

Marking: Company name or trademark  , model designation and the Recognized Component Mark for Canada,



Last Updated on 2017-11-29

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".